

About Us

Welcome to MSG Logistics Truck Body Solutions, your trusted partner for customized truck body manufacturing. We are dedicated to delivering high-quality solutions that meet the diverse needs of our clients across various industries.

OUR SERVICES

- Custom Design and Engineering
- Tailored designs, 3D modeling, and structural solutions.
- Manufacturing and Fabrication
- Types of Truck Bodies
- Painting and Finishing
- Installation and Assembly
- Maintenance and Repair
- After-Sales Support
- Consulting and Training
- Compliance and Certification

These services ensure high-quality, reliable, and customized truck body solutions for various industries.

OUR FIRM GRIP ON SYSTEMS MAKES US PROMINENT

Contact U

Address: Plot no MB-92, Hamriyah Free Zone Phase 2, Sharjah United Arab Emirates Email: msg@logistics.com, Tel: +971544919115 Web: www.msglogistics.com




80 TON LOW BED TRAILER SPECIFICATIONS	
CLIENT:	
DIMENSIONS	TOTAL WIDTH = 3.5 m TOTAL LENGTH = 16.37 m DECK LENGTH = 1.8 m GOOSENECK = 3.75 m
	FLOOR HEIGHT = 1.2 m DECK HEIGHT = 1.25 m (Approx.) KING PIN HEIGHT = 1.4 m (Approx.)
	BEAVER TAIL = 0.5 m
WEIGHTS	KINGPIN LOAD = 28 Ton Axle Load = 64 Ton Pay Load = 80 Ton
CAPACITY	80 Ton.
GOOSENECK	Fixed type with steel chequered plate flooring.
DECK	Floor – 8mm Chq-plate supported by suitable pressed steel cross Members. Double foldable
CHASSIS	Longitudinal members of hot rolled/welded I beams and cross Members of hot rolled/pressed steel channels of Grade ASTM A572 Gr 50or equivalent. All other pressed steel channels/plates of Grade ASTM A36or equivalent.
AXLE	4 x 16-ton VBT with axle spring suspension
TYRES	16+1 nos. 12.00 x R 20" tyres
RIMS	16+1 nos. 8.50 x 20 Single Disc rims
KING PIN	3 ½" dia to SAE standard. (Interchangeable to 2" kingpin)
LANDING GEAR	Two speed Adjustable
BRAKES	Twin line drum brakes, acting on -All wheels with 'S' cam actuation Two single acting diaphragm brake chambers per axle Service & emergency eelay valves Automatic load sensing valve Air reservoirManually operated parking brake.
LOADING RAMP	2 nos. 800 wide, fabricated structure covered with 6mm thick Foldable typeChequered plate and grip strips at suitable interval for safe loading/unloading, Ramps are hydraulically operated. Safety chain provided for ramp holding



LASHING RINGS	3 nos. lashing rings on either side of lowbed.
ELECTRICALS	 7-way quick release connector, pair of 24-volt rear light units, each Comprising tail light, brake and signal light fitted at rear. Side markers on either side, high intensity light at rear. Number plate lamp at rear.
ACCESSORIES	1 No. spare wheel carrier (winch type)
	1 No Fire extinguisher
	2 Nos. Foldable Manual support legs at rear.
	Reflecting stripes as per local ROP requirements (new version at Rear)
PAINTING SYSTEM	Grit blasted to S.A.2.5
	One coat of Zinc Phosphate epoxy primer and topcoat of high gloss Polyuretanefinish paint in single colour. (Customer to Specify).
INSPECTION/ TESTING	Inspection shall be carried out as per our quality standard procedure All the other procedure is as per our ITP
WARRANTY	One year from the date of delivery of product from All manufacturing defects.



GA Drawing





Address: Plot no MB-92, Hamriyah Free Zone Phase 2, Sharjah United Arab Emirate

Email: msg@logistics.com, Tel: +971544919115 Web: www.msglogistics.com